

Holographic Invisible Screen Specifications

Version: MXW-20251023

Model	MUXWAVE Transparent LED Kiosk
LED Specification	2121
Pixel Pitch (mm) (horizontal/vertical)	3.91-3.91
Pixel Density (dot/m ²)	65536
Transparency Rate	95%
Viewing Angle	Horizontal: 140°, Vertical: 140°
Module Dimension (mm) (w*h)	250x2000
Module Resolution (dot) (w*h)	64x504
Profile Dimension (mm)(w*h)	1000x2288x550
Overall Resolution (dot) (w*h)	256x504
Weight (Kg/set)	83
Brightness(cd/m ²)	≥1700 (Black Light)
Maximum Power Consumption (w/m ²)	692
Average Power Consumption (w/m ²)	332
Color Temperature(K)	3000~10000
Scanning Mode	Static Driving (Single Pixel Single Control)
Frame Rate (Hz)	60~120
Lifespan	≥ 100,000.00 hours
Pixel Configuration	16bit
Input Voltage	AC100~240V 50/60Hz
Working Voltage for Module	DC4.2V ±0.2V
Working Temperature	Temperature -20°C ~50°C
Working Humidity	Humidity 20%RH ~ 85%RH (Without Condensation)
Storage Temperature	Temperature -20°C ~60°C
Storage Humidity	Humidity 10%RH ~ 85%RH (Without Condensation)
Protection Degree	IP20
Installation Method	Floor Standing
Installation Environment	Indoor
Packing Way	Determine According to the Number of Projects

Appendix: Dimensions

